

RECEIVED
CENTRAL FAX CENTER

OCT 14 2004

XP-0985

PATENT

IN THE CLAIMS

Please amend the claims as follows.

1. (currently amended) An apparatus, comprising:
a stack of unexposed printing plates;
a vacuum system for picking up an edge of a top printing plate from the stack of printing plates; and
a peeling system including a pair of rotatable belts, wherein the stack of printing plates is located between the rotatable belts, a plurality of plate feed beams attached to, and extending between, the pair of rotatable belts, and a drive system for rotating the pair of rotatable belts to displace the plurality of plate feed beams between the top printing plate and an underlying printing plate in the stack of printing plates, thereby peeling the top printing plate from the stack of printing plates,
wherein each plate feed beam includes at least one roller attached to a shaft coupled to the plate feed beam.
2. (canceled)
3. (canceled)
4. (currently amended) The apparatus of claim ~~3~~ 1, wherein

XP-0985

PATENT

the roller is freely rotatable about the shaft.

5. (original) The apparatus of claim 1, wherein each end of each plate feed beam includes an intermediate connector, and wherein the intermediate connectors are attached to corresponding couplers located on an outer surface of the rotatable belts.

6. (original) The apparatus of claim 5, wherein each intermediate connector includes an anti-rotation device.

7. (original) The apparatus of claim 6, wherein the anti-rotation devices are configured to maintain the plate feed beams perpendicular to a tangent line of the rotatable belts.

8. (original) The apparatus of claim 6, wherein each plate feed beam includes at least one roller, and wherein the anti-rotation devices are configured to maintain the plate feed beam rollers in contact with an underside of the top printing plate.

9. (original) The apparatus of claim 6, wherein each anti-rotation device comprises a pair of protruding legs configured

XP-0985

PATENT

to cradle opposing sides of a corresponding coupler and extend partially over the outer surface of the rotatable belt on which the coupler is located.

10. (original) The apparatus of claim 1, wherein the drive system displaces the plurality of plate feed beams between a "home" position, wherein none of the plate feed beams contact the top printing plate, and a "plate loaded" position, wherein the top printing plate is completely removed from the stack of printing plates by the plate feed beams.

11. (original) The apparatus of claim 10, further comprising a sensor system for detecting when the plate feed beams are in their "home" and "plate loaded" positions.

12. (original) The apparatus of claim 11, wherein the sensor system comprises first and second shafts each including a flag, a first sensor for detecting the flag on the first shaft, and a second sensor for detecting the flag on the second shaft.

13. (original) The apparatus of claim 12, wherein the first and second shafts are biased in opposite directions.

XP-0985

PATENT

14. (original) The apparatus of claim 13, wherein the first and second shafts are spring-loaded.

15. (original) The apparatus of claim 12, wherein one of the rotatable belts includes a first boss and a second boss, wherein the first boss is configured to actuate the first shaft to displace its flag over the first sensor, thereby providing an indication that the plate feed beams are in their "home" position, and wherein the second boss is configured to actuate the second shaft to displace its flag over the second sensor, thereby providing an indication that the plate feed beams are in their "plate loaded" position.

16. (original) The apparatus of claim 15, wherein the first boss and the second boss are located on an outer surface of the rotatable belt.

17. (original) The apparatus of claim 15, wherein the first boss actuates the first shaft during a rotation of the rotatable belt by the drive system in a first direction, and wherein the second boss actuates the second shaft during a rotation of the rotatable belt by the drive system in a

XP-0985

PATENT

second, opposite direction.

18. (original) The apparatus of claim 1, wherein the plate feed beams do not contact a surface of the underlying printing plate in the stack of printing plates.

19. (original) The apparatus of claim 18, wherein the surface of the underlying printing plate comprises an emulsion.

20. (original) The apparatus of claim 1, wherein each printing plate comprises:

a substrate; and

an imageable layer formed on the substrate.

21. (original) The apparatus of claim 20, wherein the imageable layer has characteristics selected from the group consisting of: photosensitive, radiation sensitive, and thermally sensitive.

22. (original) The apparatus of claim 20, wherein the plate feed beams do not contact the imageable layer of the underlying printing plate in the stack of printing plates.

XP-0985

PATENT

23. (original) The apparatus of claim 1, wherein the rotatable belts comprises endless belts.

24. (original) The apparatus of claim 1, wherein the stack of printing plates and the peeling system are located within a cassette.

25. (original) The apparatus of claim 1, further comprising:
a media support surface;
a mounting system for mounting the top printing plate on the media support surface; and
a scanning system for imaging data onto the top printing plate.

26. (original) The apparatus of claim 25, wherein the media support surface comprises an external drum.

27. (original) The apparatus of claim 26, further including a drive system for rotating the external drum during data imaging.

XP-0985

PATENT

28. (currently amended) A method, comprising:

providing a stack of printing plates and a peeling system
both enclosed within a cassette;

picking up an edge of a top printing plate from the stack
of printing plates; and

peeling the top printing plate from the stack of printing
plates using a peeling system including a pair of rotatable
belts, a plurality of plate feed beams attached to, and
extending between, the pair of rotatable belts, and a drive
system for rotating the pair of rotatable belts to displace
the plurality of plate feed beams between the top printing
plate and an underlying printing plate in the stack of
printing plates.

29. (original) The method of claim 28, further comprising:

providing each plate feed beam with at least one freely
rotatable roller.

30. (original) The method of claim 29, further comprising:

maintaining the plate feed beam rollers in contact with
an underside of the top printing plate.

31. (original) The method of claim 28, further comprising:

XP-0985

PATENT

maintaining the plate feed beams perpendicular to a tangent line of the rotatable belts.

32. (original) The method of claim 28, further comprising:
rotating the plurality of plate feed beams between a "home" position, wherein none of the plate feed beams contact the top printing plate, and a "plate loaded" position, wherein the top printing plate is completely removed from the stack of printing plates by the plate feed beams.

33. (original) The method of claim 32, further comprising;
detecting when the plate feed beams are in their "home" and "plate loaded" positions.

34. (original) The method of claim 28, further comprising:
preventing the plate feed beams from contacting a surface of the underlying printing plate in the stack of printing plates.

35. (original) The method of claim 34, wherein the surface of the underlying printing plate comprises an imageable layer.

36. (canceled)

XP-0985

PATENT

37. (original) The method of claim 28, further comprising:
mounting the peeled top printing plate on a media support
surface; and
imaging data onto the top printing plate.

38. (original) The method of claim 37, further comprising:
rotating the media support surface during data imaging.

39. (previously presented) An apparatus, comprising:
a cassette containing a stack of unexposed printing
plates and a peeling system, wherein the peeling system is
configured to peel the top printing plate from an underlying
printing plate of the stack of printing plates without
contacting the underlying printing plate;
the peeling system including a pair of rotatable belts,
wherein the stack of printing plates is located between the
rotatable belts, a plurality of plate feed beams attached to,
and extending between, the pair of rotatable belts, and a
drive system for rotating the pair of rotatable belts to
displace the plate feed beams between the top printing plate
and the underlying printing plate in the stack of printing
plates, thereby peeling the top printing plate from the stack

XP-0985

PATENT

of printing plates.

40. (previously canceled)

41. (previously presented) An apparatus, comprising:

a stack of printing plates;

a vacuum system for picking up an edge of a top printing plate from the stack of printing plates; and

a peeling system including a pair of rotatable belts, a plurality of plate feed beams attached to, and extending between, the pair of rotatable belts, wherein each plate feed beam includes at least one freely rotatable roller attached to a shaft coupled to the plate feed beam, and a drive system for rotating the pair of rotatable belts to displace the plurality of plate feed beams between the top printing plate and an underlying printing plate in the stack of printing plates, thereby peeling the top printing plate from the stack of printing plates.

42. (previously presented) An apparatus, comprising:

a stack of printing plates;

a vacuum system for picking up an edge of a top printing plate from the stack of printing plates; and

XP-0985

PATENT

a peeling system including a pair of rotatable belts, a plurality of plate feed beams attached to, and extending between, the pair of rotatable belts, and a drive system for rotating the pair of rotatable belts to displace the plurality of plate feed beams between the top printing plate and an underlying printing plate in the stack of printing plates, thereby peeling the top printing plate from the stack of printing plates;

wherein each end of each plate feed beam includes an intermediate connector having an anti-rotation device, and wherein the intermediate connectors are attached to corresponding couplers located on an outer surface of the rotatable belts.

43. (previously presented) The apparatus of claim 42, wherein the anti-rotation devices are configured to maintain the plate feed beams perpendicular to a tangent line of the rotatable belts.

44. (previously presented) The apparatus of claim 42, wherein each plate feed beam includes at least one roller, and wherein the anti-rotation devices are configured to maintain the plate feed beam rollers in contact with an underside of the top

XP-0985

PATENT

printing plate.

45. (previously presented) The apparatus of claim 42, wherein each anti-rotation device comprises a pair of protruding legs configured to cradle opposing sides of a corresponding coupler and extend partially over the outer surface of the rotatable belt on which the coupler is located.

46. (previously presented) An apparatus, comprising:

a stack of printing plates;

a vacuum system for picking up an edge of a top printing plate from the stack of printing plates;

a peeling system including a pair of rotatable belts, a plurality of plate feed beams attached to, and extending between, the pair of rotatable belts, and a drive system for rotating the pair of rotatable belts to displace the plurality of plate feed beams between the top printing plate and an underlying printing plate in the stack of printing plates, thereby peeling the top printing plate from the stack of printing plates, wherein the drive system displaces the plurality of plate feed beams between a home position, wherein none of the plate feed beams contact the top printing plate, and a plate loaded position; and

XP-0985

PATENT

a sensor system for detecting when the plate feed beams are in their home and plate loaded positions;

wherein the sensor system comprises first and second shafts each including a flag, a first sensor for detecting the flag on the first shaft, and a second sensor for detecting the flag on the second shaft.

47. (previously presented) The apparatus of claim 46, wherein the first and second shafts are biased in opposite directions.

48. (previously presented) The apparatus of claim 47, wherein the first and second shafts are spring-loaded.

49. (previously presented) The apparatus of claim 46, wherein one of the rotatable belts includes a first boss and a second boss, wherein the first boss is configured to actuate the first shaft to displace its flag over the first sensor, thereby providing an indication that the plate feed beams are in their home position, and wherein the second boss is configured to actuate the second shaft to displace its flag over the second sensor, thereby providing an indication that the plate feed beams are in their plate loaded position.

XP-0985

PATENT

50. (previously presented) The apparatus of claim 49, wherein the first boss and the second boss are located on an outer surface of the rotatable belt.

51. (previously presented) The apparatus of claim 49, wherein the first boss actuates the first shaft during a rotation of the rotatable belt by the drive system in a first direction, and wherein the second boss actuates the second shaft during a rotation of the rotatable belt by the drive system in a second, opposite direction.